# HULK EARTH ANCHORS

## HPU-23 HYDRAULIC POWER UNIT

**HULKガソリン駆動油圧パワーユニットは、すべてのHULK油圧機器およびプロセスに動力を供給するために推奨される動力源です。140バールの圧力、毎分45リットルの流量の18HPと23HPのバリエーションがあり、HULK SH40-32アンカー打撃ハンマー、PT-150確認試験用ジャッキ、LB- 1アースシステムに最適です。**
**•エンジン回転数は電子的に制御され、最大毎分45リットルの出力容量を提供します。**
**•低燃費と低騒音のオートアイドリング機能。**
**•Quartz Hour Meterはエンジンの運転時間を記録します。**
**•ハンドルを取って持ち上げるとき、サイドは折り畳めます。**
**•35-AHの密閉された部分はメンテナンスはしないでください。**
**•圧力潤滑システムを備えた電動始動エンジン。**
**•油圧タンク内のオイルゲージ付きフィルターは簡単に交換可能。**



provides up to 45 litres per minute output capacity.

- Auto idle feature for lower fuel consumption and reduced noise levels.
- Quartz hour meter records engine run time.
- Lift and latch handle, and fold up side handles.
- 35-AH no maintenance better in enclosed compartment.
- Electric start engine with pressure lubrication system.
- In tank hydraulic filter with dipstick and easy access filter replacement.

| SPECIFICATIONS | | |
|---|---|---|
| | **HULK HPU-18** | **HULK HPU-23** |
| **Output Capacity** | 20 or 30 lpm (5 or 8 gpm) | 30 or 45 lpm (8 or 12 gpm) |
| **Pressure** | 140 Bar (2000 psi) | 140 Bar (2000 psi) |
| **Circuit Type** | Open Center | Open Center |
| **Hydraulic Reservoir** | 11 Litres (3 Gallons) | 11 Litres (3 Gallons) |
| **Couplers** | HTMA Flush Face | HTMA Flush Face |
| **Fuel Tank** | 20.8 Litres (5.5 Gallons) | 26.5 Litres (7 Gallons) |
| **Engine** | B&S 18HP Vangard | B&S 23HP Vangard |
| **Weight** | 150 kg (330 lbs) | 154 kg (340 lbs) |
| **Length** | 89cm (35”) | 89cm (35”) |
| **Width** | 55cm (21.5”) | 55cm (21.5”) |
| **Height** | 74cm (29”) | 74cm (29”) |
| **Heat Rejection** | 5 hp | 5 hp |

www.hulkearthanchors.com
www.arandr.com.au
1300 MyAncor (692626)
info@arandr.com.au

© 2014 Anchoring Rope And Rigging Pty Ltd, Australian Design Registration No. 351550, Patent Pending